



**INDUSTRIAL**

**PROTECTIVE GLOVES**

*made in EU*

*&*

*developed in EU*

## AntiCut SMOKE



EN 388:2016+A1:2018

Abrasion resistance	4
Cut resistance Coupe test	X
Tear resistance	4
Puncture resistance	3
Cut resistance TDM	D

EN ISO 13997 is 16,3 N (Newton)

Material: BRINIX® A1SM

Size: 6, 7, 8, 9, 10, 11



Gauge 21



CE



## AntiCut K 185 SB



EN 388:2016+A1:2018

Abrasion resistance	2
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	F

EN ISO 13997 is 36,7 N (Newton)

Material: BRINIX® AK185

Size: 6, 7, 8, 9, 10, 11



Gauge 18



CE



## AntiCut K 155



EN 388:2016+A1:2018

Abrasion resistance	2
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	F

EN ISO 13997 is 36,7 N (Newton)

Material: BRINIX® AK155

Size: 6, 7, 8, 9, 10, 11



Gauge 13



CE



## AntiCut BAX



EN 388:2016+A1:2018

Abrasion resistance	4
Cut resistance Coupe test	X
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	E

EN ISO 13997 is 24,3 N (Newton)

Material: BRINIX® A1BAX  
Size: 6, 7, 8, 9, 10, 11



Gauge 18



CE



EN 407:2020



Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X

## SharpKing SKY STEEL SB



EN 388:2016+A1:2018

Abrasion resistance	3
Cut resistance Coupe test	4
Tear resistance	4
Puncture resistance	3
Cut resistance TDM	F

EN ISO 13997 is 35,4 N (Newton)

Material: BRINIX® SH1SSB  
Size: 6, 7, 8, 9, 10, 11



Gauge 13



CE

## Panzerhand URSUS



EN 388:2016+A1:2018

Abrasion resistance	4
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	1
Cut resistance TDM	F

EN ISO 13997 is 96,9 N (Newton)

Material: BRINIX® P1U  
Size: 6, 7, 8, 9, 10, 11



Gauge 7



CE



EN 407:2020

Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



## AntiCut AMX



EN 388:2016+A1:2018

Abrasion resistance	2
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	D

EN ISO 13997 is 17,0 N (Newton)

Material: BRINIX® A1A

Size: 6, 7, 8, 9, 10, 11



Gauge 10



CE



EN 407:2020

Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



## AntiCut SURPRISE



EN 388:2016+A1:2018

Abrasion resistance	X
Cut resistance Coupe test	X
Tear resistance	X
Puncture resistance	X
Cut resistance TDM	D

Material: BRINIX® A1SUR

Size: 6, 7, 8, 9, 10, 11



Gauge 13



CE

## AntiCut AMX STEEL



EN 388:2016+A1:2018

Abrasion resistance	3
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	F

EN ISO 13997 is 43,8 N (Newton)

Material: BRINIX® A1AS

Size: 6, 7, 8, 9, 10, 11



Gauge 10



CE



EN 407:2020

Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



# AntiCut SHADOW



EN 388:2016+A1:2018

Abrasion resistance	3
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	F

EN ISO 13997 is 74,5 N (Newton)

Material: BRINIX® A1SH

Size: 6, 7, 8, 9, 10, 11



Gauge 10



EN 407:2004

Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



# SharpKing FINE STEEL



EN 388:2016+A1:2018



Abrasion resistance	3
Cut resistance Coupe test	4
Tear resistance	4
Puncture resistance	2
Cut resistance TDM	F

EN ISO 13997 is 63,4 N (Newton)

Material: BRINIX® SH1FS

Size: 6, 7, 8, 9, 10, 11



Gauge 13



# SharpKing BLUE



EN 388:2016+A1:2018

Abrasion resistance	2
Cut resistance Coupe test	5
Tear resistance	4
Puncture resistance	X
Cut resistance TDM	C

EN ISO 13997 is 10,7 N (Newton)

Material: BRINIX® SH1

Size: 6, 7, 8, 9, 10, 11



Gauge 13



EN 407:2004

Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



# AntiHeat TOKYO



EN 388:2016+A1:2018

Abrasion resistance	2
Cut resistance Coupe test	4
Tear resistance	4
Puncture resistance	4
Cut resistance TDM	C

EN ISO 13997 is 15,7 N (Newton)

Material: BRINIX® A1TO

Size: 6, 7, 8, 9, 10, 11



Gauge 7



EN 407:2020

Limited flame spread	4
Contact heat	3
Convective heat	3
Radiant heat	X
Small drops of molten metal	X
Large quantities of molten metal	X



# AntiCut REX



EN 388:2016+A1:2018

Abrasion resistance	4
Cut resistance Coupe test	1
Tear resistance	2
Puncture resistance	1
Cut resistance TDM	A

Material: BRINIX® M1REX

Size: 6, 7, 8, 9, 10, 11



Gauge 18



# CONDUCTIVE



EN 388:2016+A1:2018

Category I.  
Minimal risks  
Superficial mechanical injury  
ESD protection

Material: BRINIX® CON

Size: 6, 7, 8, 9, 10, 11



**MIRO GLOVES s.r.o.**

Borova 275, 569 82 Borova, Czech Republic, tel.: +420 607 847 847, mail: sales@anticut.com

[www.anticut.com](http://www.anticut.com)



[www.gloves.cz](http://www.gloves.cz)