



THERMOHAND SB BLUE



THE MANUFACTURER PROVIDED INFORMATION

PRODUCT DESIGN	Knitted work glove with coating on palm and fingers			
SIZE	7, 8, 9, 10, 11			
MATERIAL	BRINIX® M1THSB			
STANDARDS	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks EN 407:2020 Protective gloves and other hand protective equipments against thermal risks (heat and/or fire) EN 511:2006 Protective gloves against cold			
PROTECTION LEVEL	 EN 388:2016 + A1:2018		 EN 407:2020	
	Abrasion resistance	4	Limited flame spread	X
	Cut resistance Coupe test	1	Contact heat	1
	Tear resistance	2	Convective heat	X
	Puncture resistance	1	Radiant heat	X
	Cut resistance TDM	X	Small drops of molten metal	X
			Large quantities of molten metal	X
 EN 511:2006				
Convective cold		X		
Contact cold		1		
Water permeability		X		
PICTOGRAMS	 basic information for the determination of general requirements for gloves  suitable for food contact The product is manufactured in accordance with Regulation (EU) 2016/425.		 mark of EU conformity	
MARKING	- individual glove is marked on the label sewn into the hem - 10 pairs are packed in a PE bag together with information (in English) - 100 pairs are packed in a cardboard box (up to 15 kg)			

MIRO GLOVES S.R.O., GEN. PIKY 319/14, 779 00 OLOMOUC
 PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
 WWW.ANTICUT.COM



DIRECTIONS FOR USE	<ul style="list-style-type: none"> - gloves for work in operations with a risk of scratching, tearing and cutting - gloves for work in contact heat risks that must not exceed the value specified in class 1 of EN 407:2020 - gloves must not come in contact with a naked flame if no flame protection is claimed - protection levels only apply to the complete product with all layers - gloves are designed to work under normal conditions and when in contact with objects that are below -20°C - gloves lose their capabilities when cut, torn, frayed or excessively contaminated - gloves are not resistant to soaking, the glove can lose its insulating properties when wet, long-term use of the glove leads to a decrease in thermal insulation - do not use the gloves when there is a risk of getting caught by the moving parts of machinery
MAINTENANCE INSTRUCTIONS	<ul style="list-style-type: none"> - gloves can be washed repeatedly at 60°C and dried in a dryer using the basic program - store only in a dry place - dispose of contaminated products - the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards
NOTIFIED BODY	Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR
EU DECLARATION OF CONFORMITY	at the company's website: www.anticut.com

MIRO GLOVES S.R.O., GEN. PIKY 319/14, 779 00 OLOMOUC
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM

