



K155



THE MANUFACTURER PROVIDED INFORMATION

PRODUCT DESIGN	Knitted work glove		
SIZE	6, 7, 8, 9, 10, 11		
MATERIAL	BRINIX® AK155		
STANDARDS	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks		
PROTECTION LEVEL	 EN 388:2016+A1:2018		Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design. <i>EN ISO 13997 is 36,7 N (Newton)</i>
	Abrasion resistance	2	
	Cut resistance Coupe test	5	
	Tear resistance	4	
	Puncture resistance	2	
	Cut resistance TDM	F	
PICTOGRAMS	 basic information for the determination of general requirements for gloves		 mark of EU conformity
	 suitable for food contact The product is manufactured in accordance with Regulation (EU) 2016/425.		
MARKING	- individual glove is marked on the label sewn into the hem - 10 pairs are packed in a PE bag together with information (in English) - 100 pairs are packed in a cardboard box (up to 15 kg)		
DIRECTIONS FOR USE	- gloves for work in operations with a risk of scratching, tearing and cutting - gloves lose their capabilities when cut, torn, frayed or excessively contaminated - gloves are not resistant to soaking - do not use the gloves when there is a risk of getting caught by the moving parts of machinery		
MAINTENANCE INSTRUCTIONS	- gloves can be washed repeatedly at 60°C and dried in a dryer using the basic program - store only in a dry place - dispose of contaminated products - the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards		
NOTIFIED BODY	Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR		
EU DECLARATION OF CONFORMITY	at the company's website: www.anticut.com		

MIRO GLOVES S.R.O., RASINOVA 103/2, CZ – 602 00 BRNO
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM

