



# TOKYO



## THE MANUFACTURER PROVIDED INFORMATION

<b>PRODUCT DESIGN</b>	Protective mittens, the outside layer is made of the NOMEX fibre and the inner layer is the loop wave cotton insert. The mittens are designated as a protection against contact heat of 250°C.			
<b>SIZE</b>	6-11			
<b>MATERIAL</b>	BRINIX® AITO			
<b>STANDARDS</b>	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks EN 407:2020 Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)			
<b>PROTECTION LEVEL</b>	 <b>EN 388:2016 + A1:2018</b>		 <b>EN 407:2020</b>	
	Abrasion resistance	2	Limited flame spread	4
	Cut resistance Coupe test	4	Contact heat (10°C increase)	3
	Tear resistance	4	Convective heat (24°C increase)	3
	Puncture resistance	4	Radiant heat (24°C increase)	X
	Cut resistance TDM	C	Small drops of molten metal (40°C increase)	X
	<i>EN ISO 13997 is 15,7 N (Newton)</i>		<b>Large quantities of molten metal</b>	X
Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design.				
<b>PICTOGRAMS</b>	 basic information for the determination of general requirements for gloves		 mark of EU conformity	
The product is manufactured in accordance with Regulation (EU) 2016/425.				
<b>MARKING</b>	<ul style="list-style-type: none"> <li>- individual glove is marked on the label sewn into the hem</li> <li>- 10 pairs are packed in a PE bag together with information (in English)</li> <li>- 100 pairs are packed in a cardboard box (up to 15 kg)</li> </ul>			
<b>DIRECTIONS FOR USE</b>	<ul style="list-style-type: none"> <li>- gloves for work in operations with a risk of scratching, tearing and cutting</li> <li>- gloves for work in contact heat risks that must not exceed the value specified in class 3 of EN 407: 2020</li> <li>- the impact of a large quantities of melted metal can cause the ignition of internal cotton layers that are not treated with flame retardant</li> <li>- gloves are made to be quickly removed in an emergency</li> <li>- gloves lose their capabilities when cut, torn, frayed or excessively contaminated</li> <li>- gloves are not resistant to soaking and are not intended for use in wet environments</li> <li>- do not use the gloves when there is a risk of getting caught by the moving parts of machinery</li> <li>- gloves must not come in contact with a naked flame if no flame protection is claimed</li> <li>- protection levels only apply to the complete product with all layers</li> </ul>			
<b>MAINTENANCE INSTRUCTIONS</b>	<ul style="list-style-type: none"> <li>- gloves can be washed repeatedly at 60°C and dried in a dryer using the basic program</li> <li>- store only in a dry place</li> <li>- dispose of contaminated products</li> <li>- the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards</li> </ul>			
<b>NOTIFIED BODY</b>	Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR			
<b>EU DECLARATION OF CONFORMITY</b>	at the company's website: <a href="http://www.anticut.com">www.anticut.com</a>			

**MIRO GLOVES S.R.O., RASINOVA 103/2, CZ – 602 00 BRNO**  
**PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY**  
**WWW.ANTICUT.COM**

