



SINGER



THE MANUFACTURER PROVIDED INFORMATION

PRODUCT DESIGN	Knitted work glove																								
SIZE	6, 7, 8, 9, 10, 11																								
MATERIAL	BRINIX® AIS																								
STANDARDS	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks EN 407:2004 Protective gloves against heat risks																								
PROTECTION LEVEL	 EN 388:2016 + A1:2018  EN 407:2004																								
	<table border="1"> <tr> <td>Abrasion resistance</td> <td>3</td> <td>Behaviour at burning</td> <td>X</td> </tr> <tr> <td>Cut resistance Coupe test</td> <td>3</td> <td>Contact heat</td> <td>1</td> </tr> <tr> <td>Tear resistance</td> <td>4</td> <td>Convective heat</td> <td>X</td> </tr> <tr> <td>Puncture resistance</td> <td>1</td> <td>Radiant heat</td> <td>X</td> </tr> <tr> <td>Cut resistance TDM</td> <td>C</td> <td>Small sprinkles of melted metal</td> <td>X</td> </tr> <tr> <td><i>EN ISO 13997 is 12,1 N (Newton)</i></td> <td></td> <td>Large quantities of melted metal</td> <td>X</td> </tr> </table>	Abrasion resistance	3	Behaviour at burning	X	Cut resistance Coupe test	3	Contact heat	1	Tear resistance	4	Convective heat	X	Puncture resistance	1	Radiant heat	X	Cut resistance TDM	C	Small sprinkles of melted metal	X	<i>EN ISO 13997 is 12,1 N (Newton)</i>		Large quantities of melted metal	X
	Abrasion resistance	3	Behaviour at burning	X																					
	Cut resistance Coupe test	3	Contact heat	1																					
	Tear resistance	4	Convective heat	X																					
	Puncture resistance	1	Radiant heat	X																					
	Cut resistance TDM	C	Small sprinkles of melted metal	X																					
<i>EN ISO 13997 is 12,1 N (Newton)</i>		Large quantities of melted metal	X																						
Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design.																									
PICTOGRAMS	 basic information for the determination of general requirements for gloves	 mark of EU conformity																							
	The product is manufactured in accordance with Regulation (EU) 2016/425.																								
MARKING	<ul style="list-style-type: none"> - individual glove is marked on the label sewn into the hem - 10 pairs are packed in a PE bag together with information (in English) - 100 pairs are packed in a cardboard box (up to 15 kg) 																								
DIRECTIONS FOR USE	<ul style="list-style-type: none"> - gloves for work in operations with a risk of scratching, tearing and cutting - gloves do not protect from pricking, puncture etc. - gloves for work in contact heat risks that must not exceed the value specified in class 1 of EN 407:2004 - gloves lose their capabilities when cut, torn, frayed or excessively contaminated - gloves are not resistant to soaking - do not use the gloves when there is a risk of getting caught by the moving parts of machinery 																								
MAINTENANCE INSTRUCTIONS	<ul style="list-style-type: none"> - gloves can be washed repeatedly at 60°C and dried in a dryer using the basic program - store only in a dry place - dispose of contaminated products - the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards 																								
NOTIFIED BODY	Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR																								
EU DECLARATION OF CONFORMITY	at the company's website: www.anticut.com																								

MIRO GLOVES S.R.O., GEN. PIKY 319/14, 779 00 OLOMOUC
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM

