ZITTRONE



THE MANUFACTURER PROVIDED INFORMATION

<table>
<tr><td>PRODUCT DESIGN</td><td>Knitted work sleeve</td></tr>
<tr><td>SIZE</td><td>10 cm, 15 cm, 20 cm, 25 cm, 30 cm, 35 cm, 40 cm, 45 cm, 50 cm, 56 cm</td></tr>
<tr><td>MATERIAL</td><td>BRINIX® SH1Z</td></tr>
<tr><td>STANDARDS</td><td>EN ISO 21420:2020 Protective gloves. General requirements and test methods
EN 388:2016+A1:2018 Protective gloves against mechanical risks
EN 407:2004 Protective gloves against heat risks</td></tr>
<tr><td>PROTECTION LEVEL</td><td>EN 388:2016 + A1:2018 EN 407:2004
<table>
<tr><td>Abrasion resistance</td><td>2</td><td>Behaviour at burning</td><td>X</td></tr>
<tr><td>Cut resistance Coupe test</td><td>5</td><td>Contact heat</td><td>1</td></tr>
<tr><td>Tear resistance</td><td>4</td><td>Convective heat</td><td>X</td></tr>
<tr><td>Puncture resistance</td><td>2</td><td>Radiant heat</td><td>X</td></tr>
<tr><td>Cut resistance TDM</td><td>C</td><td>Small sprinkles of melted metal</td><td>X</td></tr>
<tr><td colspan="2">EN ISO 13997 is 11,5 N (Newton)</td><td>Large quantities of melted metal</td><td>X</td></tr>
</table>
Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design.</td></tr>
<tr><td>PICTOGRAMS</td><td>basic information for the determination of general requirements for gloves
CE mark of EU conformity
The product is manufactured in accordance with Regulation (EU) 2016/425.</td></tr>
<tr><td>MARKING</td><td>- individual sleeve is marked on the label sewn into the hem
- 10 pairs are packed in a PE bag together with information (in English)
- 100 pairs are packed in a cardboard box (up to 15 kg)</td></tr>
<tr><td>DIRECTIONS FOR USE</td><td>- sleeves for work in operations with a risk of scratching, puncture, tearing and cutting
- sleeves for work in contact heat risks that must not exceed the value specified in class 1 of EN 407:2004
- sleeves lose their capabilities when cut, torn, frayed or excessively contaminated
- sleeves are not resistant to soaking
- do not use the sleeves when there is a risk of getting caught by the moving parts of machinery
- gloves must not come in contact with a naked flame if no flame protection is claimed</td></tr>
<tr><td>MAINTENANCE INSTRUCTIONS</td><td>- sleeves must not be washed or tumble-dried
- store only in a dry place
- dispose of contaminated products
- the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards</td></tr>
<tr><td>NOTIFIED BODY</td><td>Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR</td></tr>
<tr><td>EU DECLARATION OF CONFORMITY</td><td>at the company’s website: www.anticut.com</td></tr>
</table>

MIRO GLOVES S.R.O., GEN. PIKY 319/14, 779 00 OLOMOUC
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM