K185 SB



THE MANUFACTURER PROVIDED INFORMATION

PRODUCT DESIGN	Knitted work glove with coating on palm and fingers
SIZE	6, 7, 8, 9, 10, 11
MATERIAL	BRINIX® AK185SB
STANDARDS	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks
PROTECTION LEVEL	**EN 388:2016+A1:2018** Abrasion resistance: 4 Cut resistance Coupe test: 5 Tear resistance: 4 Puncture resistance: 2 Cut resistance TDM: F Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design. *EN ISO 13997 is 36,7 N (Newton)*
PICTOGRAMS	basic information for the determination of general requirements for gloves CE mark of EU conformity The product is manufactured in accordance with Regulation (EU) 2016/425.
MARKING	- individual glove is marked on the label sewn into the hem - 10 pairs are packed in a PE bag together with information (in English) - 100 pairs are packed in a cardboard box (up to 15 kg)
DIRECTIONS FOR USE	- gloves for work in operations with a risk of scratching, tearing and cutting - gloves lose their capabilities when cut, torn, frayed or excessively contaminated - gloves are not resistant to soaking - do not use the gloves when there is a risk of getting caught by the moving parts of machinery
MAINTENANCE INSTRUCTIONS	- gloves must not be washed or tumble-dried - store only in a dry place - dispose of contaminated products - the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards

MIRO GLOVES S.R.O., GEN. PIKY 319/14, 779 00 OLOMOUC
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM