



AMX SLEEVE

THE MANUFACTURER PROVIDED INFORMATION

PRODUCT DESIGN	Knitted work sleeve		
SIZE	10 cm, 15 cm, 20 cm, 25 cm, 30 cm, 35 cm, 40 cm, 45 cm, 50 cm, 56 cm		
MATERIAL	BRINIX® AIASSL		
STANDARDS	EN ISO 21420:2020 Protective gloves. General requirements and test methods EN 388:2016+A1:2018 Protective gloves against mechanical risks EN 407:2020 Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)		
PROTECTION LEVEL	EN 388:2016 + A1:2018		EN 407:2020
	Abrasion resistance	2	Limited flame spread
	Cut resistance Coupe test	5	Contact heat (10°C increase)
	Tear resistance	4	Convective heat (24°C increase)
	Puncture resistance	2	Radiant heat (24°C increase)
	Cut resistance TDM	D	Small drops of molten metal (40°C increase)
	<i>EN ISO 13997 is 17 N (Newton)</i>		Large quantities of molten metal
	Due to the blade blunting during the cut resistance test (6.2.), the results of the cut resistance test are only guideline values. The TDM cut resistance test (6.3) is the result of a reference design.		
PICTOGRAMS	basic information for the determination of general requirements for gloves	mark of EU conformity	
	The product is manufactured in accordance with Regulation (EU) 2016/425.		
MARKING	<ul style="list-style-type: none"> - individual sleeve is marked on the label sewn into the hem - 10 pairs are packed in a PE bag together with information (in English) - 100 pairs are packed in a cardboard box (up to 15 kg) 		
DIRECTIONS FOR USE	<ul style="list-style-type: none"> - sleeves for work in operations with a risk of scratching, tearing and cutting - sleeves for work in contact heat risks that must not exceed the value specified in class 1 of EN 407: 2020 - sleeves lose their capabilities when cut, torn, frayed or excessively contaminated - sleeves are not resistant to soaking - do not use the sleeves when there is a risk of getting caught by the moving parts of machinery - sleeves must not come in contact with a naked flame if no flame protection is claimed - protection levels only apply to the complete product with all layers 		
MAINTENANCE INSTRUCTIONS	<ul style="list-style-type: none"> - sleeves can be washed repeatedly at 60°C and dried in a dryer using the basic program - store only in a dry place - dispose of contaminated products - the specified maintenance guarantees the stability of the required properties substantial for the assessment of conformity with the aforementioned technical standards 		
NOTIFIED BODY	Notified Body No. 2369, VIPO a.s., gen.Svobodu 1069/4, 958 01 Partizanske, SR		
EU DECLARATION OF CONFORMITY	at the company's website: www.anticut.com		

MIRO GLOVES S.R.O., RASINOVA 103/2, CZ – 602 00 BRNO
PREMISES: BOROVA 275, CZ - 569 82 BOROVA U POLICKY
WWW.ANTICUT.COM

